



UMM/EX UMM/EX/DT UMM/EX/VT

Mulcher with fixed teeth rotor for excavators having a weight between 20 and 30 t.

Standard equipment: 90 cc hydraulic piston motor, double relief valve with anticavitation function, flow control system valve, hydraulic hood.

100/45cc variable control torque

hydraulic motor for the **UMM/EX/VT**.

Options: custom made attachment plate, kit DT (= double transmission), diverter valve, rotor equipped with tooth type "C/3/HD" or blade C/3.



UMM/EX

Model	Power HP	Requirements		Excavator weight		Working width inches	Weight lbs	Grinding diameter inches (max)	Teeth q.ty/type C/3+C/3/SS
	Min - Max	Flow gal/min Min - Max	Pressure PSI Min - Max	t Min Max	t Min Max				
UMM/EX 125	120 - 160	34 - 47	3500 - 5000	20 - 30	53	3506	12	26+2	
UMM/EX 150	120 - 160	34 - 47	3500 - 5000	20 - 30	62	3726	12	32+2	

UMM/EX/DT

Model	Power HP	Requirements		Excavator weight		Working width inches	Weight lbs	Grinding diameter inches (max)	Teeth q.ty/type C/3+C/3/SS
	Min - Max	Flow gal/min Min - Max	Pressure PSI Min - Max	t Min - Max	t Min - Max				
UMM/EX/DT 125	140 - 200	66 - 100	3500 - 5000	20 - 30	53	3506	12	26+2	
UMM/EX/DT 150	140 - 200	66 - 100	3500 - 5000	20 - 30	62	3726	12	32+2	

UMM/EX/VT Hydraulic motor with variable torque

Model	Power HP	Requirements		Excavator weight		Working width inches	Weight lbs	Grinding diameter inches (max)	Teeth q.ty/type C/3+C/3/SS
	Min - Max	Flow gal/min Min - Max	Pressure PSI Min - Max	t Min - Max	t Min - Max				
UMM/EX/VT 150	120 - 160	34 - 55	3500 - 5000	20 - 30	62	3726	12	32+2	

Data refers to the machine without options.



Tooth type C/3 (standard)



Tooth type C/3/HD (option)



Tooth blade type C/3 (option)



Tooth type C/3/SS (side scraper)